


PEDESTAL DRILLING MACHINES

AJ 25/30/32/40/50/70



This range of machines incorporate all geared heads, fully immersed in oil, and are designed for heavy duty, long life operation. The gears in the speed change box are hardened and shaved, and manufactured from the best quality nickel chrome steel. Shafts are splined and ground, and made to close tolerances to ensure perfect alignment and smooth operation. Automatic oiling of all essential moving parts is achieved by an automatic pressure oil pump. All machines, with the exception of the AJ 25 and AJ 30, are fitted as standard with an automatic feed mechanism which is graduated and can be preset to the desired depth. (Feed optional of AJ 25 & AJ 30).



| CAPACITY | AJ 25 | AJ 30 | AJ 32 | AJ 40 | AJ 50 | AJ 70 |
|----------------------------------------------------------------------------------------------------|---------------------------------|---------------------------------|-------------------------------------------------|--------------------------------------------------|------------------------------------------------|---------------------------------------------------|
| Drilling Capacity in | | | | | | |
| Mild Steel (mm) | 25 | 30 | 32 | 40 | 50 | 70 |
| Spindle Taper | | | | | | |
| (Morse Taper) | 3 | 3 | 4 | 4 | 4 | 5 |
| Distance from Spindle | | | | | | |
| to Column (mm) | 250 | 250 | 300 | 350 | 400 | 420 |
| Distance from Spindle | | | | | | |
| to Table min/max (mm) | 0 - 820 | 0 - 820 | 70 - 885 | 70 - 885 | 70 - 820 | 70 - 777 |
| Distance from spindle | | | | | | |
| to base max (mm) | 1,220 | 1,220 | 1,245 | 1,197 | 1,290 | 1,300 |
| TABLE | | | | | | |
| Rotation of Table to Head | 360° | 360° | 360° | 360° | 360° | 360° |
| Tilting of Table | N/A | N/A | 180° (opt) | 180° (opt) | 180° | 180° |
| Table Size (mm) | 380 x 400 | 380 x 400 | 400 x 420 | 480 x 480 | 550 x 550 | 600 x 600 |
| FEEDS AND SPINDLE | | | | | | |
| Maximum Spindle Traverse | | | | | | |
| (hand/power)(mm) | 120 | 120 | 160 | 180 | 260 | 300 |
| Number of Spindle Speeds | 8 | 8 | 8 | 8 | 9 | 12 |
| Range of Spindle Speeds | | | | | | |
| (rpm) | 65 - 3,060 | 65 - 3,060 | 75 - 2,100 | 93 - 1,420 | 45 - 1,115 | 35 - 1,238 |
| Power Feed Rates | Manual | Manual | 0.10 - 0.2 | 0.10 - 0.18 | 0.08 - 0.16 | 0.05 - 0.10 |
| (mm/rev) | (power opt) | (power opt) | - 0.3 | - 0.24 | - 0.24 - 0.35 | -0.15 - 0.20 |
| | | | | | - 0.35 - 0.5 | |
| BASE / COLUMN | | | | | | |
| Base Size Overall (mm) | 400 x 655 | 400 x 655 | 655 x 492 | 755 x 480 | 1,060 x 600 | 730 x 1,190 |
| Column Diameter (mm) | 110 | 110 | 125 | 150 | 200 | 220 |
| SPEEDS AND MOTORS | | | | | | |
| Main Motor Power | 1.6Hp | 1.9Hp | 1/1.5Hp | 2Нр | 4Нр | 7.5 Hp |
| | (1.2 kW) | (1.4 kW) | (1.1kW) | (1.5 kW) | (3 kW) | (5.5 kW) |
| Coolant Pump Motor | opt | opt | 0.1 Hp | 0.1 Hp | 0.1 Hp | 0.2 Hp |
| | | | (0.075 kW) | (0.075 kW) | (0.075 kW) | (0.15 kW) |
| WEIGHT AND DIMENSIONS | | | | | | |
| Overall Height (mm) | 2,030 | 2,030 | 2,296 | 2,363 | 2,547 | 3,200 |
| Nett Weight (kg) | 260 | 260 | 292 | 435 | 900 | 1,150 |
| 0 \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\ | 310 | 320 | 392 | 565 | 1,090 | 1,390 |
| Gross Weight (kg) | | | | | | |
| Case Dimensions (mm) | 600 x 800 | 600 x 800 | 600 x 1000 | 680 x 1,050 | 760 x 1,250 | 880 x 1,380 |
| Main Motor Power Coolant Pump Motor WEIGHT AND DIMENSIONS Overall Height (mm) Nett Weight (kg) | (1.2 kW) opt 2,030 260 | (1.4 kW) opt 2,030 260 | (1.1kW) 0.1 Hp (0.075 kW) 2,296 292 | (1.5 kW) 0.1 Hp (0.075 kW) 2,363 435 | (3 kW) 0.1 Hp (0.075 kW) 2,547 900 | (5.5 kW) 0.2 Hp (0.15 kW) 3,200 1,150 |

TECHNICAL SPECIFICATIONS

Ajax Machine Tools International Ltd Unit 360, Ampress Lane, Ampress Park, Lymington, Hampshire, UK SO41 8JX Telephone: +44 (0)1590 676000 Fax: +44 (0)1590 676001





